

**Fan W3G250 230V 50/60Hz 1.25A f/Heatmaster compact**

Article number: 40-10-3951

**Dimensions**

Length	413.00 mm
Width	322.00 mm
Height	136.00 mm
Actual weight	3.498 kg

**Basic data**

Montiert	Mounted
Thermal protection contact	Yes
Type	Flange
Weight	3.5 kg

**Rated values**

Phases	1 Ph
Nominal frequency [Hz]	50/60 Hz
Control	0-10 V / PWM

**Classification**

IP protection rating	IP44
----------------------	------

**Dimensions**

Height	86.5 mm
Total depth	130 mm
Diameter	320 mm
Other dimension	295 mm

**Rated values 50 Hz**

Elektrische Nennleistung	0.17 kW
Nominal voltage single-phase	230 V
Voltage tolerance	10 - 20 %
Nominal current single-phase	1,25 A
Speed	3050 U/min
Ambient temperature	-25 - 60 °C
Sound power level Lw	82 dB
Sound pressure level Lp	74 dB

**Volumetric flow rate 50 Hz**

Characteristic curve – 0 Pa	1305 m <sup>3</sup> /h
Characteristic curve – 70 Pa	1150 m <sup>3</sup> /h
Characteristic curve – 140 Pa	965 m <sup>3</sup> /h
Characteristic curve – 200 Pa	615 m <sup>3</sup> /h

**Rated values 60 Hz**

Elektrische Nennleistung	0.17 kW
Nominal voltage single-phase	230 V
Voltage tolerance	10 - 20 %
Nominal current single-phase	1,25 A
Speed	3050 U/min
Ambient temperature	-25 - 60 °C
Sound power level Lw	82 dB
Sound pressure level Lp	74 dB

**Volumetric flow rate 60 Hz**

Characteristic curve – 0 Pa	1305 m <sup>3</sup> /h
Characteristic curve – 70 Pa	1150 m <sup>3</sup> /h
Characteristic curve – 140 Pa	965 m <sup>3</sup> /h
Characteristic curve – 200 Pa	615 m <sup>3</sup> /h