

**Fan FC056-6DT 8850m³ 400V 323W 0.8A f/tube**

Article number: 60-47-9556

**Basic data**

Montiert	Mounted
Thermal protection contact	Yes
Type	Installation in pipe
Chimney	560 - BD 580

Rated values

Phases	3 Ph
Nominal frequency [Hz]	50 Hz
Control	Frequency converter (with all-pole sinusoidal filter) / Transformer / Triac

Classification

IP protection rating	IP54
Certifications	CE
Insulation class (DIN EN 60085)	F
Efficiency rating (ErP)	E15

Rated values 50 Hz

Elektrische Nennleistung	0.36 kW
Nominal voltage delta connection	230 V
Nominal voltage star connection	400 V
Nominal current delta connection	1,3 A
Nominal current star connection	0,74 A
Speed	890 U/min
Power factor	0.7



Rated values 50 Hz

Ambient temperature	-40 - 40 °C
Sound power level L _w	73 dB
Sound pressure level L _p	48 dB

Volumetric flow rate 50 Hz

Characteristic curve – 0 Pa	10000 m ³ /h
Characteristic curve – 10 Pa	9700 m ³ /h
Characteristic curve – 20 Pa	9300 m ³ /h
Characteristic curve – 30 Pa	8800 m ³ /h
Characteristic curve – 40 Pa	8300 m ³ /h
Characteristic curve – 50 Pa	7600 m ³ /h