



Fan FC040-4EQ 4000m³ 230V 260W 1.2A ErP

Article number: 60-47-9141



Dimensions

Length	540.00 mm
Width	516.00 mm
Height	208.00 mm
Actual weight	10.395 kg

Basic data

Montiert	Mounted
Thermal protection contact	Yes
Type	Installation at a wall

Rated values

Phases	1 Ph
Nominal frequency [Hz]	50 Hz
Control	Frequency converter (with all-pole sinusoidal filter) / Transformer / Triac

Classification

IP protection rating	IP54
Certifications	CE
Insulation class (DIN EN 60085)	F
Efficiency rating (ErP)	E15

Dimensions

Width	490 mm
Height	540 mm



Dimensions

Total depth	211 mm
Diameter	466 mm

Rated values 50 Hz

Elektrische Nennleistung	0.26 kW
Nominal voltage single-phase	230 V
Nominal current single-phase	1,2 A
Speed	1370 U/min
Ambient temperature	-25 - 40 °C
Sound power level L _w	74 dB
Sound pressure level L _p	49 dB

Volumetric flow rate 50 Hz

Characteristic curve – 0 Pa	4656 m ³ /h
Characteristic curve – 10 Pa	4537 m ³ /h
Characteristic curve – 20 Pa	4414 m ³ /h
Characteristic curve – 30 Pa	4286 m ³ /h
Characteristic curve – 40 Pa	4159 m ³ /h
Characteristic curve – 50 Pa	4014 m ³ /h
Characteristic curve – 60 Pa	3846 m ³ /h
Characteristic curve – 70 Pa	3667 m ³ /h
Characteristic curve – 80 Pa	3451 m ³ /h
Characteristic curve – 90 Pa	3240 m ³ /h

Spec. power 50 Hz

Characteristic curve – 0 Pa	46.1 W/(1000m ³ /h)
Characteristic curve – 10 Pa	48 W/(1000m ³ /h)
Characteristic curve – 20 Pa	51 W/(1000m ³ /h)
Characteristic curve – 30 Pa	52.9 W/(1000m ³ /h)
Characteristic curve – 40 Pa	55.7 W/(1000m ³ /h)
Characteristic curve – 50 Pa	58.6 W/(1000m ³ /h)
Characteristic curve – 60 Pa	62.3 W/(1000m ³ /h)
Characteristic curve – 70 Pa	66.3 W/(1000m ³ /h)
Characteristic curve – 80 Pa	70.7 W/(1000m ³ /h)
Characteristic curve – 90 Pa	75.6 W/(1000m ³ /h)