

**Fan 4E30 GP40 BCU**

Article number: 40-20-1920

**Dimensions**

Length	451.00 mm
Width	447.00 mm
Height	276.00 mm
Actual weight	8.966 kg

**Basic data**

Montiert	Mounted
Thermal protection contact	Yes

**Rated values**

Phases	1 Ph
Nominal frequency [Hz]	50 Hz
Control	Triac / Transformer

**Classification**

IP protection rating	IP55
Certifications	CE
Insulation class (DIN EN 60085)	F

**Rated values 50 Hz**

Elektrische Nennleistung	0.1 kW
Nominal voltage single-phase	230 V
Nominal current single-phase	0,55 A
Speed	1400 U/min



## Rated values 50 Hz

Ambient temperature

-25 - 40 °C

## Volumetric flow rate 50 Hz

Characteristic curve – 0 Pa	2350 m <sup>3</sup> /h
Characteristic curve – 10 Pa	2200 m <sup>3</sup> /h
Characteristic curve – 20 Pa	2090 m <sup>3</sup> /h
Characteristic curve – 30 Pa	1960 m <sup>3</sup> /h
Characteristic curve – 40 Pa	1830 m <sup>3</sup> /h
Characteristic curve – 50 Pa	1700 m <sup>3</sup> /h