



Fan f/circulation air unit CL-60-920

Article number: 60-43-4051



Basic data

Montiert	Mounted
Thermal protection contact	Yes

Rated values

Phases	1 Ph
Nominal frequency [Hz]	50/60 Hz
Control	Frequency converter (with all-pole sinusoidal filter) / Transformer / Triac

Classification

IP protection rating	IP54
Certifications	CE
Insulation class (DIN EN 60085)	F
Efficiency rating (ErP)	E15

Rated values 50 Hz

Elektrische Nennleistung	0.12 kW
Nominal voltage single-phase	230 V
Nominal current single-phase	0,62 A
Speed	1440 U/min
Ambient temperature	-25 - 70 °C
Sound power level Lw	69 dB
Sound pressure level Lp	44 dB



Volumetric flow rate 50 Hz

Characteristic curve – 0 Pa	2204 m ³ /h
Characteristic curve – 10 Pa	2124 m ³ /h
Characteristic curve – 20 Pa	2037 m ³ /h
Characteristic curve – 30 Pa	1924 m ³ /h
Characteristic curve – 40 Pa	1809 m ³ /h
Characteristic curve – 50 Pa	1685 m ³ /h
Characteristic curve – 60 Pa	1537 m ³ /h
Characteristic curve – 70 Pa	1372 m ³ /h
Characteristic curve – 80 Pa	1180 m ³ /h

Rated values 60 Hz

Elektrische Nennleistung	0.17 kW
Nominal voltage single-phase	230 V
Nominal current single-phase	0,76 A
Speed	1690 U/min
Ambient temperature	-25 - 70 °C